

Healthcare Privacy Curtains

Technical Specifications



Overview	Milliken Specialty Interiors provides drapery for healthcare facilities today. Most privacy curtains are made from 100% polyester in order to meet industry flammability specifications. We have a healthy amount of options: from union shade dobbys to cat/disperse jacquards so we can design fabrics that are both easy on the eye and wallet.	
Fibers	Polyester (Disperse and Cationic)	
Width	72"	
Flammability	2010 NFPA 701	Pass
Performance	Bow and Skew ASTM D-3882	Max 2"
	Tensile Strength ASTM D-5034	Min 125 lbf Warp x 75 lbf Fill
	Seam Slippage ASTM D-4034	Min 25 lbf Warp x 25 lbf Fill
	Wash Shrinkage AATCC 135	Max 2.5% Warp x 2.5% Fill
	160 °F (1 & 5 Wash Cycles)	
	Wash Fastness AATCC 61	Min 3.5 Polyester / 3.5 Cotton
	160 °F with Polyester mesh	
	120 °F with Nylon mesh	
	Solvent Bleed AATCC 132	Min Grade 4
	Resistance to Crocking AATCC 8	Min Grade 4 wet / 4 dry
	Colorfastness to Light AATCC 16	Min Grade 4 @ 40 hrs



Features Wonder



Features Squared Away

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.
 © Copyright 2017 Milliken & Company. All rights reserved. The Milliken mark and Milliken logo are trademarks of Milliken & Company.