

# Hospitality Drapery

## Technical Specifications



<b>Overview</b>	Milliken Specialty Interiors provides drapery for commercial spaces, hotels and theaters throughout the country. One of the most important specification in commercial drapery is the flammability requirement NFPA 701. Meeting FR guidelines for textiles is a core competency and we have years of experience delivering woven and knit fabrics that pass these tough specifications.	
<b>Fibers</b>	Polyester	
<b>Width</b>	54", 60", 72"	
<b>Flammability</b>	2010 NFPA 701	Pass
<b>Performance</b>	Bow and Skew ASTM D-3882	Max 1.5"
	Tensile Strength ASTM D-5034	Min 125 lbf Warp x 75 lbf Fill
	Seam Slippage ASTM D-4034	Min 25 lbf Warp x 25 lbf Fill
	Wash Shrinkage AATCC 135 120 °F (1 & 5 Wash Cycles)	Max 2.5% Warp x 2.5% Fill
	Wash Fastness AATCC 61	Min 3.5 Polyester / 3.5 Cotton
	Resistance to Crocking AATCC 8	Min Grade 3 wet / 3 dry
	Colorfastness to Light AATCC 16	Min Grade 4 @ 40 hrs
	Solvent Bleed AATCC 132	Min Grade 4



Features Encore



Photo courtesy of Eric Laignel

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.  
© Copyright 2017 Milliken & Company. All rights reserved. The Milliken mark and Milliken logo are trademarks of Milliken & Company.