

Hospitality Upholstery

Technical Specifications



Overview	Milliken Specialty Interiors offers upholstery fabrics that can be used in the hospitality market. With years of experience in the office sector, we know how to design fabrics that are built to last. We understand that a beautifully designed fabric is worthless if it will not meet the end use performance expectations.	
Fibers	Polyester and blends	
Width	54"	
Flammability	CAL TB 117 (Class 1)	Pass
Performance	Resistance to Pilling ASTM D-3511	Min Class 3
	Bow and Skew ASTM D-3882	Max 2"
	Tensile Strength ASTM D-5034	Min 50lbf Warp x 50 lbf Fill
	Tongue Tear Strength ASTM D-5735	Min 10 lbf
	Seam Slippage ASTM D-4034	Min 25 lbf Warp x 25lbf Fill
	Dynamic Seam Fatigue ASTM D-4033	Min 5,000 cycles
	Abrasion - Wyzenbeek ASTM D-4157	Min 60,000 cycles
	Resistance to Crocking AATCC 8	Min Grade 3.5 wet / 4 dry
	Colorfastness to UV Light AATCC 16	Min Grade 4 @ 40 hrs



Features Crossroad



Features Gauge

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.
 © Copyright 2017 Milliken & Company. All rights reserved. The Milliken mark and Milliken logo are trademarks of Milliken & Company.