Home Upholstery

Technical Specifications



Overview Milliken Specialty Interiors creates fabrics that make a house feel like a home. Fabrics that look and feel

bespoke, but stand up to spilled wine, pillow forts and movie night. Fabrics that meet — and, in many cases, exceed — industry regulations. Fabrics that are as good for the environment as they are for your brand.

Fibers Cotton, polyester, and blends

Width 54"

Repellency* Spray Rating AATCC 22 Min 80 out of 100

Liquid Repellency AATCC 193 Average 3 of 5

Flammability CAL TB 117 NFPA 260 UFAC Pass

Performance Soil Release AATCC 130 Min 3 out of 5

Spot Cleaning (Internal test) Min 3 out of 5

Resistance to Crocking AATCC 8 Grade 3 wet / 4 dry

Colorfastness to Light AATCC 16 Min 4 out of 5
Colorfastness to Laundering AATCC 61 Min 3-4 out of 5
Colorfastness to Drycleaning AATCC 132 Min 3-4 out of 5
Colorfastness to Bleach ASTM TS-001 Min 4 out of 5

Tongue Tear Strength ASTM D-2261 Min 4 lbs
Tensile Strength ASTM D-5034 Min 50 lbs
Seam Slippage ASTM D-4034 Min 25 lbs

Wyzenbeek ASTM D-4157 cotton duck Min 15,000 (heavy duty)

Pilling Resistance Martindale ASTM D4966-98 Min 4 out of 5

Dimensional Change after home laundering Min -4% to max 2% Dimensional Change after dry cleaning Min -4% to max 2%

Environment* Achieved third party GREENGUARD Gold certification

No Added Flame Retardants

No Fluorine or fluorine derivatives

^{*} Indicates properties of Breathe by Milliken™ Fabrics, a specialty interiors fluorine-free fabric